

Têtes de sécurité

					Types	Codes	Poids (kg)	Nbre par palette	Poids par pal. (kg)																														
Tête de sécurité					D 300	8630	320	2 unités sur 2 chevrons																															
<table border="1"> <thead> <tr> <th>Diamètre tuyau</th> <th>A (mm)</th> <th>B (mm)</th> <th>C (mm)</th> </tr> </thead> <tbody> <tr> <td>300</td> <td>550</td> <td>1380</td> <td>560</td> </tr> <tr> <td>400</td> <td>660</td> <td>1710</td> <td>680</td> </tr> <tr> <td>500</td> <td>860</td> <td>2150</td> <td>860</td> </tr> <tr> <td>600</td> <td>980</td> <td>2460</td> <td>980</td> </tr> <tr> <td>800</td> <td>1200</td> <td>3095</td> <td>1200</td> </tr> </tbody> </table>					Diamètre tuyau	A (mm)	B (mm)	C (mm)	300	550	1380	560	400	660	1710	680	500	860	2150	860	600	980	2460	980	800	1200	3095	1200	D 400	8640	490	2 unités sur 2 chevrons							
Diamètre tuyau	A (mm)	B (mm)	C (mm)																																				
300	550	1380	560																																				
400	660	1710	680																																				
500	860	2150	860																																				
600	980	2460	980																																				
800	1200	3095	1200																																				
					D 500	8642	850	2 unités sur 2 chevrons																															
					D 600	8644	1150	1 unité sur 1 chevron																															
					D 800	8654	1970	1 unité sur 1 chevron																															
Tête de Pont					Hauteur 0,60 m	8569	110	-	-																														
					Hauteur 0,80 m	8659	177	-	-																														
<table border="1"> <thead> <tr> <th>Hauteur (mm)</th> <th>A (mm)</th> <th>B (mm)</th> <th>D tuyau femelle</th> <th>D tuyau mâle</th> </tr> </thead> <tbody> <tr> <td>600</td> <td>1000</td> <td>400</td> <td>200</td> <td>200/300</td> </tr> <tr> <td>800</td> <td>1200</td> <td>450</td> <td>300</td> <td>300/400</td> </tr> <tr> <td>1000</td> <td>1450</td> <td>500</td> <td>300/400</td> <td>300 à 500</td> </tr> <tr> <td>1300</td> <td>1 800</td> <td>720</td> <td>300 à 600</td> <td>300 à 800</td> </tr> <tr> <td>1650</td> <td>2 400</td> <td>855</td> <td>300 à 800</td> <td>300 à 1000</td> </tr> </tbody> </table>					Hauteur (mm)	A (mm)	B (mm)	D tuyau femelle	D tuyau mâle	600	1000	400	200	200/300	800	1200	450	300	300/400	1000	1450	500	300/400	300 à 500	1300	1 800	720	300 à 600	300 à 800	1650	2 400	855	300 à 800	300 à 1000	Hauteur 1,00 m	8657	285	-	-
Hauteur (mm)	A (mm)	B (mm)	D tuyau femelle	D tuyau mâle																																			
600	1000	400	200	200/300																																			
800	1200	450	300	300/400																																			
1000	1450	500	300/400	300 à 500																																			
1300	1 800	720	300 à 600	300 à 800																																			
1650	2 400	855	300 à 800	300 à 1000																																			
					Hauteur 1,30 m	8658	567	-	-																														
					Hauteur 1,65 m	8662	920	-	-																														

• Prière de préciser le CODE ARTICLE sur les documents de commande.